


EXCOOL CDU DATA CENTER COOLING SOLUTION

Precision engineered liquid cooling.



Capacity

400kW – 1500kW

Premium 316-grade stainless steel construction

Precision engineering using premium 316-grade stainless steel ensuring erosion resistance and longevity.

Dual hygienic flanged connection points

Installation flexibility with dual top and bottom hygienic flanged connection points.

Built-in electrical redundancy

Dual power feed connections with a built-in Automatic Transfer Switch (ATS) for complete electrical redundancy.

Remote monitoring and diagnostics

Evaluate system performance and diagnose issues in real-time with remote monitoring from the local BMS or Excool HQ.

In-built controls redundancy

UPS-backed controls system, providing comprehensive visibility and immediate response to black building events.

Hot-swappable componentry

Minimise operational downtime with hot-swappable fluid filtration system and pump components.

Fluid integrity monitoring

Intelligent fluid quality monitoring providing frequent system health check and diagnostics.

Versatile compatibility

Suitable for use with water, PGW and EGW mixes for flexible system configuration.



High-density cooling for HPC and AI

Specifically designed for current and future high-performance computing and AI applications.

Lightning fast response

Immediate control of instantaneous AI load activation through integrated system communication.

Intelligent controls package

Optimised group control with an advanced operational sequence, giving precise thermal stability at the highest efficiency.

Versatile operation

Expansion vessel fitted to allow for a range of operational temperatures depending on computational requirements.

Cost-efficient investment

With low CAPEX requirements, we provide a financially accessible solution without compromising on quality or functionality.



Frame size 1: 400kW - 800kW

Model	EX-CDU-400
Nominal flow rate	160 GPM
External pressure drop	50psi
Approach temp delta	3.6degF to 7degF
Number of pumps	2 (N+1)
Frequency	50Hz/60Hz
Phases	3 + N + E
Compatible fluids	Glycol, water
Maximum power input	6.5kW
Primary/secondary filtration	From 20-500µm
Primary/secondary pipework connections	Flanged, top and bottom
Dimensions	Height: 80in Depth: 47in Width: 35in
Dry weight	1984lbs
Operating weight	2425lbs

Frame size 2: 800kW - 1500kW

Model	EX-CDU-1000
Nominal flow rate	415 GPM
External pressure drop	50psi
Approach temp delta	3.6degF to 7degF
Number of pumps	2 (N+1)
Frequency	50Hz/60Hz
Phases	3 + N + E
Compatible fluids	Glycol, water
Maximum power input	15kW
Primary/secondary filtration	From 20-500µm
Primary/secondary pipework connections	Flanged, top and bottom
Dimensions	Height: 80in Depth: 47in Width: 47in
Dry weight	3307lbs
Operating weight	3969lbs

Please note this data sheet represents maximum values with all components operating at 100% capacity. This data sheet is not based on any specific outdoor ambient condition.

Excool HQ. Bromsgrove, Worcestershire, B60 4EA | Tel: +44 (0) 1527 492750 | Email: info@excool.com | www.excool.com